FS.D

BONDING

POINT



Earthing Point

ESDBP

Description

Designed specifically for use on racks, cabinets and trolleys etc. Used for the grounding personnel, typically for those who need to be mobile or on cabinets for use by Field Service Engineers. Small dimensions, 25mm x 35mm allows it to be used where space is limited. Connects to known good earth via solder tag. ESDP has 1 x 10mm stud and no resistor.

Features

- Designed to be fixed to the work bench.
- Fitted with 3 x 1 Meg Ohm Resistor for each connection.
- 3 connection points.
- Configurations can include 4mm,7mm,10mm Stud, 4mm Banana Sockets, M5 Binding Post.
- Supports EN 61340-5-1 & ESD S20.20 ESD Handling.

Earth bonding points and plugs can be manufactured using any combination of the following:

5) Hole blank.

- 1) M5 post. 2) 4mm stud.
- 3) 10mm stud.
- 4) 7mm stud.

6) Safety banana socket. 7) Black banana socket. 8) Reverse banana socket.

 1
 2
 3
 4
 5

 2
 3
 4
 5

 2
 0
 0
 0
 0

 6
 7
 8
 9

 0
 0
 0
 0

Custom grounding products can be manufactured on request. Special customised printing available on request.



Important Notice: The information contained within this spec sheet is for guidance only. We make no warranties expressed or implied and assume no liability regarding any use of this information. Earthing Point, February 24th 2020.