



**Specification for Printable PVC Heavy Duty Self Adhesive Tape
 Part- FMT33**



Product Description	Clear transparent UPVC film coated with: clear transparent natural rubber buff coloured natural rubber white coloured natural rubber and hydrocarbon resin adhesive		
Width	50mm		
Length	66m		
Film Colour	Clear	Buff	White
Film Thickness (Microns μ)	Average: 58.0 μ Min: 52.2 μ Max: 63.8 μ		
Weight of Adhesive (g/sq.m)	Average: 22.5 Min: 20.5 Max: 24.5		
Total Thickness (Microns μ)	Average: 80.5 Min: 72.7 Max: 88.3		
Elongation at break (%)	Average: 70.0 Min: 40.0 Max: 100.0		
Tensile Strength (N/cm)	Average: 60.0 Min: 40.0 Max: 80.0		
Peel Adhesion (N/cm)	Average: 2.3 Min: 1.8 Max: 2.8	Average: 2.5 Min: 2.0 Max: 3.0	Average: 2.5 Min: 2.0 Max: 3.0

Stocking time: We recommend using the product within 6 months from the delivery

Stocking Conditions: The product has to be stocked in a dry environment, at a temperature between 21°C and 50°C. The product must be stored protected from dust, humidity and direct sun exposure. It must be stored horizontally and kept in the original packaging

Use: Prior to use, carefully check that the contact surfaces are totally dry and clean from oil, grease and dust. If the storage temperature has been different from what suggested, bring the tape to the temperature before application.

The information contained within this spec sheet is for guidance only. We make no warranties expressed or implied and assume no liability regarding any use of this information. (Re-view July 15)

