

Printable PVC Heavy Duty Self Adhesive Tape

FMT33

Description

Clear transparent UPVC film coated with: clear transparent natural rubber buff coloured natural rubber white coloured natural rubber and hydrocarbon resin adhesive.



Properties	Typical Values		
Width	50mm		
Length	66m		
Film Colour	Clear	Buff	White
Film Thickness (Microns μ)	Average: 58.0μ Min: 52.2 μ Max: 63.8 μ		
Weight of Adhesive (g/sq.m)	Average: 22.5 Min: 20.5 Max: 24.5		
Total Thickness (Microns μ)	Average: 80.5 Min: 72.7 Max: 88.3		
Elongation at break (%)	Average: 70.0 Min: 40.0 Max: 100.0		
Tensile Strength (N/cm)	Average: 60.0 Min: 40.0 Max: 80.0		
Peel Adhesion (N/cm)	Average: 2.3 Min: 1.8 Max: 2.8	Average: 2.5 Min: 2.0 Max: 3.0	Average: 2.5 Min: 2.0 Max: 3.0



Printable PVC Heavy Duty Self Adhesive Tape

FMT33

Stocking Time:

We recommend using the product within 6 months from the delivery.

Stocking Conditions:

The product has to be stocked in a dry environment, at a temperature between 21°C and 50°C. The product must be stored protected from dust, humidity and direct sun exposure. It must be stored horizontally and kept in the original packaging.

Meets the Following ESD Standards & Regulations:

-  RoHS compliant
-  REACH compliant
-  CE approved
-  IEC 61340-5-1

Use:

Prior to use, carefully check that the contact surfaces are totally dry and clean from oil, grease and dust. If the storage temperature has been different from what suggested, bring the tape to the temperature before application.



Eliminate Costly Static Damage...

Whether you are experiencing unacceptable levels of damage in transit, need a specific cleanroom solution or simply don't know which ESD safe equipment is best for you, we can help!

Request complimentary, no obligation advice by speaking with one of our technical experts today.

