



Specification of Floor Marking Tape

Part- FT2

FT2 is a clear permanent adhesive featuring excellent UV resistance and weatherability together with good adhesive performance, even on apolar substrates. The adhesive complies with the European food directives and legislations, FDA 175.105 and the German recommendations XIV as published by BFR. BFR is the German federal institute for risk assessment. The adhesive can be used in direct contact with dry and moist, non-fatty foodstuffs.

Promotional labels and stickers for in- and outdoor use offering good durability and weatherability. Further applications include labels and plastic bottles for cosmetics, household chemicals and motor oil. Conversion and dispensing characteristics have proven to meet present day market requirements.

Face stock

A gloss white monomeric, plasticized, cadmium free PVC film.
Basis Weight 114g/m² ISO 536
Caliper 0.083mm ISO 534

Adhesive

A general purpose permanent, acrylic based adhesive.

Liner

Basis weight 65g/m² ISO 536
Caliper 0.057mm ISO 534
Transparency 46% ISO 534

Laminate

Total Caliper 0.154

Performance Data

Initial Tack 420 N/m FTM 9 glass
Peel Adhes. 90° 250N/m FTM2 st.st
Min. appl. Temp. +5°C
Service temp -20°C --> +80°C

Shelf Life

Two years, stored at 22°C

(All data to be considered as typical values.)

The information contained within this spec sheet is for guidance only. We make no warranties expressed or implied and assume no liability regarding any use of this information. (Re-view July 15)

